

### REMARKS

Applicants respectfully request, pursuant to 37 C.F.R. §1.125, to substitute the original Specification of the above-captioned U.S. Patent Application (a U.S. Continuation Application) with a new Specification that is an English-language translation of the Finnish-language Specification of the PCT Application (PCT/FI99/00564) which is the parent of the above-captioned U.S. Continuation Application. An explanation of the reasons for filing the present request is provided below, along with reasons why this request should be granted.

A Declaration that details the circumstances surrounding the filing of the present request is attached hereto. Also attached are a true and verified Translation of the Finnish-language PCT Application.

As discussed in the attached Declaration signed by Ms. Sirpa Kuisma, a European Patent Attorney who is fluent in both Finnish and English, Applicants have filed the present request because, after comparing the Specification of the above-captioned U.S. Continuation Application with the above-referenced parent of the present application (i.e. the Finnish-language PCT Application), Applicants discovered some inconsistency between the two documents. The Declaration also discusses why the inconsistency is present, and explains why the Specification of the true and verified Translation, attached hereto, should be substituted for the original Specification.

As detailed in the attached Declaration, Ms. Kuisma's European law firm had taken over the responsibilities of the Application discussed herein from a previous agent

of the Assignee of this Application. When reviewing the file of the PCT application, Ms. Kuisma discovered that the previous agent had filed a Finnish Application (FI981485) on June 26, 1998. Ms. Kuisma also discovered that, on June 24, 1999, the previous agent had filed a PCT Application, in Finnish, in the Finnish Patent Office acting as the Receiving Office, claiming priority from the Finnish Patent Application. Ms. Kuisma then discovered that the previous agent had filed what was supposed to be an English translation of the PCT Application in the Swedish Patent Office acting as the International Search Authority on August 26, 1999.

When Ms. Kuisma compared the English translation filed with the Swedish Patent Office and the Finnish-language PCT Application, she found that the subject matter contained in these two documents was not identical. Rather, the subject matter in the English translation corresponded to the subject matter previously contained in the Finnish Patent Application, rather than the PCT Application.

As explained in the attached Declaration, it appears that the translator who prepared the English translation filed on August 26, 1999 had not been made aware by the previous agent that the Finnish Patent Application was not identical to the Finnish-language PCT Application. Hence, the translator prepared a translation of the Finnish Patent Application rather than of the PCT Application. This has resulted in the current Specification of the above-captioned U.S. Continuation Application not being fully consistent with the Specification of the parent PCT Application.

In order to correct this situation, Ms. Kuisma has prepared and verified the Translation attached hereto. The attached Translation is a translation of the Finnish-language PCT Application discussed above, and not of the Finnish Patent Application. Applicants submit that no new matter has been added, as the attached Translation is a verified translation of the parent PCT Application. Applicants therefore respectfully request that the attached Translation be entered as a Substitute Specification in the above-captioned U.S. Continuation Application.

Therefore, for at least the reasons discussed above, Applicants respectfully submit that the present request to enter the substitute specification should be granted, and that the Specification included in the Translation attached hereto be substituted for the current Specification of the above-captioned U.S. Continuation Application. Additional evidence in support of the present Petition are provided below.

Applicants respectfully submit that it is clear from the prosecution history of the U.S. Continuation Application that it was Applicants' intent to file a translation of the Finnish-language PCT Application, not of the Finnish Patent Application, in the U.S. This intent is particularly clear in view of the fact that, on February 23, 2000, a Request for Continuation of an International Application Under 37 C.F.R. §1.53(b) had been filed with the U.S. Patent Office, listing PCT/FI99/00564, not the Finnish Patent Application, as the parent Application.

Applicants also submit that the filing of a translation of the wrong document was purely the result of a clerical error, having no deceptive intent associated therewith. As

discussed in the attached Declaration, and as shown in the attached Translation, only a small portion of the text in the Finnish Patent Application was modified to generate the Finnish-language PCT Application. Therefore, it is clear that an administrative oversight by Applicants' previous agent resulted in the filing of a translation of the Finish Patent Application rather than a translation of the parent PCT Application. Applicants point out, however, that upon having discovered the error, Applicants' current representatives have acted diligently in attempting to correct it.

In addition to the above, Applicants submit that the Finnish-language PCT Application was filed with the Finnish Patent Office, an internationally-recognized entity that granted Applicants an internationally-recognized filing date. Further, Applicants point out that public access to the Finnish-language PCT Application is available at the International Bureau under PCT Rule 94.1(b). Hence, a verifiable and credible record exists of what subject matter Applicants originally attempted to protect in the PCT Application and of when protection for this subject matter was first sought. Therefore, Applicants respectfully submit that they are not presently attempting to add subject matter that was not previously disclosed in the documents upon which the present U.S. Continuation Application claims priority. Rather, Applicants are merely attempting to incorporate subject matter into the present U.S. Continuation Application that should have been included therein from the outset. As such, Applicants respectfully submit that no new matter is being added.

Applicants further submit that, under 35 U.S.C. §371(c), “[a]n international application designating the United States shall have the effect, from its international filing date under article 11 of the treaty, of a national application for patent regularly filed in the Patent and Trademark Office”. At least in view of this section of the Code, Applicants respectfully submit that, in the case at hand, the above-discussed Finnish-language PCT Application effectively became the U.S. Continuation Application. Hence, correcting the Specification of the U.S. Continuation Application using the attached Translation does not constitute the addition of new matter. Rather, the subject matter being added as part of the correction has been a part of the present U.S. Continuation Application from the outset, simply in a different language.

Applicants have supported that the subject matter contained in the attached Translation is what Applicants intended to file as the U.S. Continuation Application discussed herein. Applicants have also supported that the present Petition has been filed pursuant to the detection of a clerical error that involved no deceptive intent. Further, Applicants have shown that, under 35 U.S.C. §371(c), all of the information contained in the attached Translation is already part of the U.S. Continuation Application, just in a different language.

Furthermore, Applicants submit that the International Bureau has available records supporting the fact that the attached Translation contains no subject matter that was not previously included in the Finnish-language PCT Application. Therefore, for at least the reasons discussed above, Applicants respectfully request that the present request to enter

the substitute specification be granted and that the Specification portion of the attached Translation of the Finnish-language PCT Application be substituted for the original Specification.

If any additional fees are due with respect to the filing of this paper, please charge Counsel's Deposit Account Number 50-2222.

Respectfully submitted,



---

Majid S. Albassam  
Registration No. 54,749

**Customer No. 32294**  
SQUIRE, SANDERS & DEMPSEY LLP  
14<sup>TH</sup> Floor  
8000 Towers Crescent Drive  
Tysons Corner, Virginia 22182-2700  
Telephone: 703-720-7800  
Fax: 703-720-7802

MSA:mmi

Enclosures: Declaration Supporting Amendment pursuant to 37 C.F.R. § 1.125  
Verified Translation of PCT Application  
Clean copy of substitute Specification  
Marked-up Copy of substitute Specification

## **Management of packet switched connections in a—mobile communications network**

### **Field of the invention**

5           The present invention concerns connection management in a communications system, especially in a mobile communications system suitable for packet switched data transmission.

### **Technical background**

10           Telecommunication networks can be divided into circuit switched and packet switched networks. In circuit switched networks, the transmission connection between the transmitting party and the receiving party is reserved before starting the transmission. It is a drawback of this connection method that the transmission connection is reserved even if no information is  
15           transmitted over the connection. In packet switched networks, transmission of packets may be connection-oriented or connectionless. In connectionless packet switched networks, the transmission network is common to all users. Information is transmitted in packets which contain information on their destination. Resources of the transmission network are not reserved in  
20           advance, nor are any packets transmitted when there is no information to be transmitted. In this way no transmission network capacity is reserved unnecessarily. In the connection-oriented packet switched technology, virtual circuits are formed for certain transmission routes between network elements and every packet of the connection is routed along the same route. Thus, the  
25           information is routed as in circuit switched networks, but no transmission capacity is unnecessarily reserved. E.g. the ATM (Asynchronous Transfer Mode) network is formed with the aid of virtual circuits.

          Accessing packet switched networks like the Internet is further possible in many ways. The pan-European GSM mobile communications  
30           system, which is based on time division multiple access TDMA, allows circuit switched connection to packet switched networks in a known manner, when an adaptation protocol (e.g. a point-to-point protocol, PPP) is used between the mobile station and the connection point located in the network. The GPRS service (General Packet Radio Service) defined in the GSM system also  
35           allows packet switched connection from mobile stations to packet data networks like the Internet. Figure 1 shows the simplified structure of the GPRS

network. The serving GPRS support node SGSN contains mobility management and safety functions of the mobile stations. Through the gateway GPRS support node GGSN the network transmits packet data to and receives packet data from a packet data network PDN. By way of the gateway  
5 node the GPRS network is also in connection with other networks, such as the Internet or an X.25 network. Both the gateway and the serving node contain IP routing functions. Base station subsystem BSS includes base station controller BSC and one or more base stations BS. Mobile station MS is in connection with a base station over the radio path. In addition, the network  
10 includes home location register HLR for permanent storing of subscriber information.

In the GPRS network, transmission of packets between the mobile station and the serving node is transparent from the viewpoint of the base station system, and no record relating to the mobile station's GPRS service is  
15 stored in the base station system. Instead, every serving node SGSN has context information about the mobile stations which it is serving. In the GPRS system, context information can be divided into mobility management MM and packet data protocol PDP information respectively. The mobility management will tell where the mobile station is located and in which state it is. Possible  
20 states of a mobile station registered with a GPRS system are the idle state, the standby state and the ready state. When in the idle state, the mobile station is passive and it is able to receive only the broadcast of the base stations, but no point-to-point packets can be transmitted between the mobile station and the network. In the ready state, the mobile station is able to receive packets  
25 without any call procedure. From the ready state the mobile station moves to the standby state after a certain non-activity period. From the standby state the mobile station returns to the ready state after a call from the network or for transmission of a packet. The move between idle state and active state takes place by GPRS Attach and GPRS Detach procedures. In the ready state, the  
30 network knows the location of the mobile station with one-cell precision. Each packet to the mobile station is routed individually with the aid of a cell identifier attached to the packet from the serving node to the correct base station. Thus, user information is transmitted between the network and the mobile station without any connection assigned between the base station system and the  
35 serving node SGSN.



Figure 2 shows a new third generation (3G) mobile communications system which is based e.g. on WCDMA (Wideband Code Division Multiple Access) technology. The 3G mobile communications system combines packet data transmission functionality with circuit switched communication. The serving node 3G SGSN corresponds to the serving node SGSN of the GPRS network, like the gateway node GGSN, which attends to connections with other packet data networks. Hereinafter in this application a serving node SGSN means the serving node of the 3G network. The mobile services switching centres 3G MSC attends to the routing of circuit switched traffic. The network may also be implemented without any mobile services switching centre 3G MSC. The subscriber information of mobile stations is stored permanently in home location register HLR and temporarily in visitor location register VLR located e.g. in connection with the mobile services switching centre, and in serving node SGSN. The radio network subsystem RNS includes a radio network controller RNC and at least one base station BS. The operation of the whole system is monitored by operation & maintenance system O&M.

In the third generation mobile communications system, the radio network subsystem must have information about mobile stations to be served over the radio interface, because the radio network subsystem allocates radio resources for the subscribers and it is able to combine both circuit switched and packet switched connections of the mobile station in the radio interface, using the same hashspreading code when e.g. WCDMA technology is used. It has been proposed that connections over the  $I_u$  interface between the radio network and the main trunk should be connection-oriented due to the said combining and coding of circuit switched and packet switched traffic. In addition, a connection set-up to be made for the packet service allows advantageous transmission to the radio network subsystem of parameters describing the quality of the service (e.g. transmission rate, transmission delay). Without a connection set-up which takes place separately, these parameters must be added separately to each packet to be transmitted. A connection between the serving node and the radio network subsystem can be implemented e.g. with ATM in such a way that for each mobile station a virtual channel is reserved according to a certain ATM adaptation layer (e.g. ATM Adaptation Layer 5 AAL5 or ATM Adaptation Layer 2 AAL2).

In order to combine circuit switched and packet switched traffic in a radio network subsystem, it is preferable to unify the mobile station state management. For this reason, an idle state and an active state are proposed as mobility management (MM) states of the mobile station registered with the 3G network. These states differing from the GPRS system are also natural states, when the transmission of packet data between the serving node and the radio network is connection-oriented, as presented above. In the idle state, the mobile station is only able to listen to the broadcast of base stations and to move into an active state through a procedure to be described later in connection with Figure 3. In the active state, the mobile station can transmit and receive data packets continuously. When the mobile station is in the active state, a communication connection has been set up between the serving node and the radio network and at least management resources are reserved for the mobile station in the radio network. Thus, each mobile station reserves network resources for use by itself in the active state. Of the presented 3G mobile communications system it is known to release limited radio resources during pauses in the packet data transmission, whereby the mobile station in the active state moves from the radio channel dedicated to the mobile station to a common radio channel, and the allocated radio resource can thus be released for other use. The connection between mobile station and base station is continued on the common channel, on which it is possible to transmit small data packets in both directions and to receive broadcast of the base station in the mobile station. When the packet data transmission is resumed, the radio network subsystem dedicates a new radio channel for the connection between base station and mobile station. The main trunk is not aware of this change of the used type of radio channel, so the mobile station's state remains active from the viewpoint of mobility management (MM).

Figure 3 shows signalling between a mobile station and a 3G mobile communication network in the beginning of a packet data transmission. To keep it simple, the figure does not show any state-of-the-art signalling between the mobile station and the radio network subsystem for setting up e.g. connections of lower layers. In the Attach procedure 31, the serving node SGSN e.g. fetches subscriber information of the mobile station from the home location register. After this procedure, the mobile station is able to transmit and receive short messages (SMS) and to listen to the broadcast of base stations,

but the mobile station is not able to transmit or receive packet data, because no packet data address is yet available to it. Hereby the mobile station is in the idle state. In PDP Context activation procedure 32, a packet data address is indicated to the mobile station, whereupon the mobile station will also be able to transmit and receive packet data. The mobile station has hereby moved into the active state. By the PDP Context activation procedure of the packet data protocol the mobile station is thus committed to a packet data address or to several addresses. Either the mobile station or the network can start this procedure. Before packet data is transmitted between the network and the mobile station, a connection-oriented communication connection is set up between serving node SGSN and radio network subsystem RNS by Bearer request/assignment procedure 33, wherein identifiers relating to the connection are transmitted, such as connection rate requirements and transmission delay requirements for the radio connection. After the communication connection has been set up between radio network subsystem RNS and serving node SGSN, it is possible to transmit packet data between the serving node SGSN and mobile station MS through radio network subsystem RNS (point 34).

In the operation of the third generation mobile communications system it is a problem as regards the transmission of packet data that resources of the transmission path between serving node SGSN and the radio network subsystem as well as memory resources of the radio network subsystem are reserved unnecessarily due to the burst-like character of packet data. Since a connection can be set up e.g. in the morning and end only in the evening, an address is reserved on the transmission path and connection management resources are reserved in the radio network subsystem for the whole day, even if no packets to be transmitted were to travel in the virtual circuit. Thus, a connection-oriented connection as described above for the serving node and the radio network subsystem consumes the transmission network's limited address space and the radio network subsystem's management resources.

### **Summary of the invention**

The objective of this invention is to save limited address space of the transmission network and to save management resources of the radio network subsystem an access system.

This objective is achieved by a method and a mobile communications system in accordance with the invention, which are characterized by that which is said in the independent claims. Advantageous embodiments of the invention are presented in the dependent claims.

5           The invention is based on the idea that the logical communication connection between the radioaccess network and the serving node of the trunk network is released while the data transmission is inoperative, and this communication connection is again set up, when transmission of user data begins. The communication connection between the radioaccess network and  
10   the serving node is released in such a way that the logical connection between the serving node and the ~~mobile station~~terminal will remain. If said communication connection between the serving node and the radioaccess network was the ~~mobile station's~~terminal's last connection, the ~~mobile station~~terminal will enter a 3 G idle state in accordance with the invention,  
15   which corresponds to the idle state of circuit switched services. While the communication connection is released in accordance with the invention, the ~~mobile station~~terminal keeps the packet data address, whereby a packet data transmission can be started to and from the ~~mobile station~~terminal. When the packet data transmission begins, a communication connection is again set up  
20   between the radioaccess network and the serving node. In a first embodiment of the invention, the communication connection is released when the inactivity of data transmission has lasted for a predetermined period of time.

It is an advantage of this kind of connection management that the limited address space of the transmission network is saved, when the  
25   addresses of inactive connections are freed for other use, and the management resources of the ~~radio network subsystem~~access system are saved.

### **Brief description of the drawings**

30           The invention will now be described in connection with advantageous embodiments and referring to the examples shown in Figures 4-10 in the appended drawings, wherein:

- Figure 1   is a block diagram of the GPRS system:  
35   Figure 2   shows such parts of the 3G mobile communications system which are essential for the invention;

- Figure 3 is a signalling diagram of the setting up of a packet data connection in the 3G mobile communications system;
- Figure 4 is a flow chart of a first embodiment of the method according to the invention;
- 5 Figure 5 is a signalling diagram of the connection management according to the invention;
- Figure 6 is a flow chart of a second embodiment of the method according to the invention;
- Figure 7 shows changes in state caused by the connection management according to the invention;
- 10 Figure 8 shows the connection management according to the invention as a theoretical layer description;
- Figure 9 is a block diagram of parts essential to the invention in a mobile communications system according to a first embodiment of the invention;
- 15 Figure 10 is a block diagram of parts essential to the invention in a mobile communications system according to a second embodiment of the invention.

## 20 Detailed description of the invention

The present invention can be applied in connection with any suitable ~~mobile~~—communications system. Hereinafter the invention is described more closely by way of example mainly in connection with a digital 3G mobile communications system with the focus on that part of the system which is intended for packet data transmission. Figure 2 shows the simplified structure of a 3G network which was described earlier.

25

In the following, the invention will be described in greater detail in the light of a first embodiment of the invention. Figure 4 is a flow chart of a first embodiment of the method according to the invention, wherein the idleness, that is, the non-activity of a mobile connection is measured by using a timer. At stage 41 a check is made of the non-activity of the user data traffic of a mobile station's communication connection. If no user data is transmitted on the connection, a timer is set at stage 42 at some suitable value, e.g. at zero or at a certain value, and the timer is started. Alternatively, the check at stage 41 can be left out, if the timer is always set and started after transmission and/or reception of a data packet. At stage 43 a check is made to see if the

30

35

idleness of the connection continues. If user data is transmitted on the connection, the process returns to stage 41 to monitor the beginning of the idleness of the connection. If the connection is found to be idle in the check made at stage 43, a check is made at stage 44 to see if the timer has achieved the pre-set trigger value. Such a trigger value may be e.g. zero or some suitable value. If the timer has not yet achieved the trigger value, monitoring of the continued idleness of the connection goes on at stage 43. If the timer has achieved the trigger value at stage 44, the mobile station's communication connection between the radio network and the serving node is disconnected at stage 45, and management resources are possibly made free in the radio network, e.g. such records relating to the mobile station that may include information on transmission rate and transmission delay requirements of the service or on frame lengths and hashspreading codes to be used at the radio interface. If one or more circuit switched connection events are taking place at the same time in the mobile station through the mobile services switching centre MSC, the disconnection of the communication connection started by the serving node SGSN will of course not affect the concerned circuit switched connection events. The user data's need for switching is checked at stage 46. When a need occurs to switch user data from the network to the mobile station or from the mobile station to the network, a communication connection is re-established (stage 47). After re-establishment of the connection, the process moves to the beginning of the flow chart to monitor the beginning of a new idleness period of the connection.

Figure 5 is a signalling diagram of the first embodiment of the invention. For the sake of simplicity, the figure does not show any such state-of-the-art signalling between the mobile station and the radio network subsystem, by which e.g. lower layer connections are set up. The procedures of stages 31-33 are carried out in a state-of-the-art manner, as was described earlier in connection with Figure 3. At stage 34 user data is switched in a state-of-the-art manner between mobile station MS and the serving node SGSN through the radio network subsystem RNS. Upon completion of the transmission of user data at stage 34 or in connection with transmission/reception of a data packet, the timer is set and it is started for the time of the idleness period of the mobile station's communication connection between the RNS and the SGSN (stage 55). If the idleness period goes on for a pre-established trigger value, signalling takes place between the mobile

station MS and the serving node SGSN concerning temporary release of the MM layer in a Release MM procedure 56. The procedure 56 is not needed, if both the network and the mobile station have a timer and the timers are synchronised with each other. After the triggering off of the timer or the performance of the Release MM procedure, disconnection takes place at stage 57 of the mobile station's communication connection between the radio network subsystem and the serving node, and management resources are possible made free in the radio network. The connection is disconnected as regards user data and signalling, or only as regards user data. The described temporary release of the MM layer will take place in case only one communication connection existed for the mobile station between the radio network and the serving node. If, on the other hand, the mobile station has several simultaneous communication connections between the radio network and the serving node, the Release MM procedure will not cause release of the MM layer, but the process goes on from stage 57 with a disconnection of the mobile station's communication connection. When a need occurs for switching of user data, re-establishment of the connection is signalled between mobile station MS and the serving node SGSN in a Reconnect MM procedure 58. The connection between radio network subsystem RNS and the serving node SGSN is re-established by a Bearer request procedure 59 known as such in the state of the art. The reconnect signalling 58 of the connection can be started either by mobile station MS or by the serving node SGSN, depending on the direction in which user data is relayed. In a state-of-the-art manner the packet is relayed at the radio interface from the base transceiver station to the mobile station MS using already reserved radio resources, or after the reservation of radio resources started by the call procedure or the mobile station, depending on the state of radio resources.

In the first embodiment of the invention, the timer and the trigger value can be set e.g. in such a way that disconnection of the connection is started after a ten-minute idleness period. The idleness period starting disconnection of the connection according to the invention can be set individually for the different connections, e.g. at some value between 1 and 10 minutes. In addition, the control of the timer's setting value may also depend on the subscribed service class. The timer may be located on the network side, preferably in connection with the serving node SGSN, or/and on the mobile station side. In the PDP Context activation procedure at stage 32 in

Figure 5 it is also possible in accordance with the invention to negotiate about the timer's trigger value, if required. Alternatively, negotiation about the trigger value may take place in connection with some other SM level procedure, when required, such as PDP Context modification or PDP Context deactivation, or  
 5 the trigger value can be stated on the broadcast channel of the base station. It is not necessary to make the trigger value known to the mobile station.

In the second embodiment of the invention, disconnection of the connection between the radio network subsystem and the serving node SGSN is triggered off by a shortness of resources at the  $I_u$  interface. In the second  
 10 embodiment of the invention, traffic monitoring is performed in the network in the same way as was described above in connection with the first embodiment of the invention. Figure 6 is a flow chart of a method according to the second embodiment of the invention. At stage 62 the activity of the mobile station's connection is monitored. At stage 63 the shortness of resources of the  $I_u$   
 15 interface between the radio network and the serving node is monitored. Alternatively, the sufficiency of resources can be checked in connection with the establishment of a new connection. If there are sufficient resources, the process returns to stage 62 to check the connection's activity. If there is a shortness of resources, the idle connection over the  $I_u$  interface is  
 20 disconnected (stage 65), whereby the address used on the connection will be made free for other use. Such a connection is preferably disconnected, which has been non-active for the longest time or which has a low priority in relation to the other connections. At stage 66 a check is made of the need for switching of user data of the disconnected connection. When a need to switch user data  
 25 occurs, the connection over the  $I_u$  interface is reconnected (stage 67). After reconnection of the connection, the process returns to the beginning of the flow chart to monitor the activity of the connection.

In a first manner of implementation of the third embodiment of the invention, the radio network subsystem RNS can prevent disconnection of a  
 30 connection over the  $I_u$  interface. Such a functionality may be needed e.g. in a situation where a mobile station has transmitted to the radio network a data packet, which the radio network subsystem has received, but of the relaying of which the serving node does not yet know. When the SM protocol starts releasing resources of the  $I_u$  connection in accordance with the invention by  
 35 the Release procedure 57 of Figure 5, RNS notifies SGSN that it does not accept the release. E.g. a 'data arriving' reason code or such may be attached



to the notification. Hereby disconnection of the connection is interrupted and it is possible to relay the data packet to the serving node. In this embodiment, the MM mobility management state is preferably changed from the active to the 3G idle state only after the disconnection of the  $I_u$  connection, so that the interrupted disconnection of the connection will not cause any change in the MM state. Otherwise, the functionality of this embodiment is similar e.g. to the functionality of the first or second embodiment described above or to a combination of the first and second embodiment.

In a second manner of implementation of the third embodiment of the invention, MS does not accept a change of the MM mobility management state to the active state as commanded by the serving node SGSN. Such a functionality may be needed e.g. in a situation where a mobile station has transmitted a data packet, of the switching of which the serving node, however, does not yet know. Hereby the SM protocol will not start any release of resources of the  $I_u$  connection.

In a third manner of implementation of the third embodiment of the invention, the serving node SGSN does not accept the change of the MM mobility management state to an idle state from an active state as commanded by the mobile station MS. Such a functionality may be needed e.g. in a situation, where the serving node has transmitted a data packet, of the switching of which the mobile station, however, does not yet know. Hereby the SM protocol will not start any release of the resources of the  $I_u$  connection.

Figure 7 shows a change of the MM state of the connection as a result of the connection management according to the invention. ~~In accordance with the state of the art, the~~ The mobile connection, which has been changed into the active state in accordance with the state of the art, will go into the 3G idle state in accordance with the invention after the disconnection of the connection at stage 57 of Figure 5. From the 3G idle state the connection goes back to the active state e.g. after the re-establishment of the connection in accordance with stage 59 of Figure 5. A performance of a state-of-the-art PDP Context activation procedure will also return the mobile connection to the active state. Both states, the active state and the 3G idle state, keep the context active in the network.

Figure 8 shows a theoretical layer description of a connection in accordance with the invention, wherein protocols, which have the same names and which belong to units connected with one another, are

communicating with each other. Of the protocols shown in the figure, the SM (Session management) performs session management, and the state-of-the-art SM-procedures relating to this are e.g. PDP Context activation, PDP Context modification and PDP Context deactivation. The MM (Mobility Management) protocol performs management of the mobile station's location and state. A state-of-the-art MM procedure is e.g. location update. According to the invention, new functions are performed for the upper level protocol, in the case shown as an example in Figure 8 for the SM level protocol, such as traffic monitoring and, based on this, temporary disconnection of the MM connection, that is, management of the  $I_u$  interface. SM level procedures in accordance with the invention are the Release MM procedure 56 and the Reconnect MM procedure 58 of Figure 5. Lower level BM (Bearer Management) and RRM (Radio Resource Management) protocols attend to management of the transmission connection, while the TT (Transmission & Transport) protocol attends to management of the physical layer. The Release procedure 57 and Bearer request procedure 59 in accordance with the invention which are known as such are in accordance with the Bearer Management protocol. After disconnection of the connection over the  $I_u$  interface in accordance with the invention, there is no MM layer or lower level connection from the serving node, but there is an upper SM (Session Management) level connection to the mobile station. The disconnection of the BM connection over the  $I_u$  interface automatically also brings about a disconnection of the TT connection. During the release of  $I_u$  resources in accordance with the invention a location update is performed in a state-of-the-art manner on the signalling connection without re-establishment of the  $I_u$  connection.

Figure 9 is a block diagram of a first embodiment of a mobile communications system implementing connection management in accordance with the invention as regards the units which are essential to the invention. The figure shows that connection management equipment of a mobile communications system according to the invention which performs disconnection of a logical communication connection between a serving node SGSN and a radio network subsystem RNS during idleness of the connection and reconnection of this communication connection when the traffic activity starts. The connection management equipment is preferably located in connection with the serving node SGSN, as is shown in Figure 9, and/or partly

in connection with the mobile station. The connection management equipment includes monitoring equipment 91 for identifying the activity and non-activity of user data traffic on the mobile station's communication connection, a timer 93 responsive to this monitoring equipment for measuring uninterrupted non-activity in the relaying of user data and state control equipment 95 for releasing the logical communication connection between the serving node SGSN and the radio network subsystem RNS, when a pre-set time has passed as measured by the timer, and for reconnection of the logical communication connection between the serving node SGSN and the radio network subsystem RNS as the relaying of user data resumes. The control 98 of the timer's setting values is obtained from elsewhere in the network, e.g. as established by the operator from an operation and management system (O&M). The connection management equipment may also include signalling equipment 97, which is used for signalling information between the serving node SGSN and the mobile station MS on release of the logical communication connection and/or on the need for its reconnection.

Figure 10 is a block diagram of a second embodiment of the mobile communications system according to the invention as regards the units which are essential to the invention. The connection management equipment is preferably located in connection with the serving node SGSN, as is shown in Figure 10, and/or partly in connection with the mobile station. In the second embodiment of the invention, the connection management equipment includes monitoring equipment 101 for identifying the activity and non-activity of user data traffic on the mobile station's communication connection, resources monitoring equipment 102 for monitoring vacant or busy connection identifiers of the connections between the serving node SGSN and the radio network subsystem RNS and state control equipment 105 for releasing the logical communication connection between the serving node SGSN and the radio network subsystem RNS, when as indicated by the resources monitoring equipment 102 there is a lack of connection identifiers and when the connection is idle as indicated by the monitoring equipment 101, and for reconnecting the logical connection between the serving node SGSN and the radio network subsystem RNS as the relaying of user data resumes. The resources monitoring equipment 102 monitors the use of connection identifiers of the transmission network's connections. The connection management equipment may also include signalling equipment 107, which

are used for signalling information between the serving node SGSN and the mobile station MS on release of the logical connection and/or on a need for its reconnection.

- 5       The drawings and the relating explanation and the names of procedures occurring therein are only intended to illustrate the inventive idea. As regards its details the connection management according to the invention may vary within the scope defined by the claims. Although the invention was described above mainly in connection with a 3G mobile system implemented with WCDMA technology, the invention may also be used for some other kind
- 10      of mobile system, e.g. for a system implemented with TD-CDMA technology. The invention is also suitable for use with the type of connectionless connection existing between a trunk network and a radio network, e.g. in a Frame Relay case. The radio network mentioned in this application may be e.g. UTRAN (UMTS Terrestrial Radio Access Network).